

**PENTANE PLUS ( C5+ )**

**KHARG PETROCHEMICAL COMPANY**

PROPERTY	UNIT	METHOD	RESULT
<i>Density at 15 °C</i>	GR/CM3	D-4052	0.64-0.67
<i>R.V.P.</i>	PSI	D-323	14 MAX
<i>Colour</i>	-	D-156	+ 25 MIN
<i>Total Sulphur</i>	PPM	IP-243	600 MAX
<i>Lead Content</i>	PPB	IP-224	40 MAX
<i>I.B.P.</i>	°C	D-86	30 MIN
<i>F.B.P.</i>	°C	D-86	160 MAX
<i>Parraffin</i>	VOL%	D-5134	84 MIN
<i>Olefin</i>	VOL%	D-5134	1 MAX
<i>Naphthene</i>	VOL%	D-5134	10 MAX
<i>Aromatic</i>	VOL%	D-5134	BALANCE MAX
<i>Copper Corrosion</i>	-	D-130	1 a
<i>Doctor Test</i>	-	IP-30	+ VE

**PORT RESTRICTIONS**

**LOAD RATE : 350 MT PER HOUR**

**JETTY RESTRICTIONS : L.O.A. 1180 FEET WITH DRAFT 38 FEET**